



12"/30cm | EFi75xx Intrinsically Safe Blower/Exhauster

- Intrinsically safe – ATEX certified for use in adverse atmosphere
- Cast aluminum turbo blade is precision balanced
- Tough, chemical resistant ABS housing, carbon-filled to conduct static charges to ground
- IP65 rain tested switch enclosure "watertight"
- Blow or exhaust hazardous/explosive gases safely
- Power cable is 30ft/9m long.
See page 48 for plug options.
- IMPA Codes:
EB7201xx (110V) - 591506, 591418, 591423
EB7201xx-230 (230V) - 591506, 591419, 591424

Optional Accessories: Anti-Static Duct,
Duct Carrying Bags

MODEL	EFi75xx
Order #	EB7201XX/EB7201XX-230
STOCK LOCATIONS	
FREE AIR	2,500cfm/4,250m ³ /hr
15ft/1-90° turn	1,664cfm/2,829m ³ /hr
15ft/2-90° turns	1,529cfm/2,599m ³ /hr
DUCT ADAPTER(S)	2
WEIGHT	44lbs/20kg
DIMENSIONS (h/w/d)	16/15/16 in 406/381/406 mm
NOISE	89dB
MOTOR	0.75Hp/0.56kW
ELECTRIC	115/230VAC, 1 ϕ , 50/60Hz
AMPS – START – RUN	115V: 37A 230V: 27A 115V: 7.2A 230V: 3A
UNIT CERTIFICATION	II 2 G Ex de IIB T6 BR-Ex de IIB T6
MOTOR CERTIFICATION	II 2 G Ex d IIB

